

A/RE

REISSUE PATENT APPLICATION TRANSMITTAL

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, D.C. 20231

Attorney Docket No.	201804
First Named Inventor	Kump
Original Patent Number	5,660,946
Original Patent Issue Date	August 26, 1997
Express Mail No.	EM196177849US

APPLICATION ELEMENTS

1. ☒ Transmittal Form with Fee
2. ☒ Specification and Claims (amended, if appropriate)
3. ☒ Drawing(s) (proposed amendments, if appropriate)
4. ☒ Reissue Oath/ Declaration (original or copy)
5. Original U.S. Patent
☒ Offer to Surrender Original Patent
or
☐ Ribbioned Original Patent Grant
☐ Affidavit/Declaration of Loss
6. Original U.S. Patent currently assigned?
☒ Yes ☐ No
(If Yes, check applicable box(es))
☒ Written Consent of all Assignees
☐ 37 C.F.R. § 3.73(b) Statement
☐ Power of Attorney

ACCOMPANYING APPLICATION PARTS

7. ☐ Transfer drawings from Patent File
8. ☐ Foreign Priority Claim
9. ☒ Information Disclosure Statement
- ☒ PTO-1449 Form
- ☒ Copies of IDS Citations
10. ☐ English Translation of Reissue Oath/
Declaration
11. ☐ Small Entity Statement(s)
- ☐ Enclosed
- ☐ Statement filed in prior application;
status still proper and desired
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard
(Should be specifically itemized)
14. ☒ Other: Request For Abstract of Title

Instructions for Calculating Claim Fees:

If Total Claims In Patent is greater than 20, use Number Filed In Reissue Application minus Total Claims In Patent; if Claims In Patent is less than 20, use Number Filed In Reissue Application minus 20.

CLAIMS AS FILED - PART 1

BASIC FEE					\$760.00
	CLAIMS IN PATENT	NUMBER FILED IN REISSUE APPLICATION	NUMBER EXTRA	RATE	
TOTAL CLAIMS	9	17	0	x\$18.00	\$-0-
INDEPENDENT CLAIMS	1	2	1	x\$78.00	\$78.00
Total of above calculations =					\$838.00
Reduction by 50% for filing by small entity =					\$
TOTAL =					\$838.00

CLAIMS AS AMENDED - PART 2

	CLAIMS REMAINING AFTER AMENDMENT	HIGHEST NUMBER PREVIOUSLY PAID FOR	EXTRA CLAIMS PRESENT	RATE	
TOTAL CLAIMS	17 –	20	0	x\$18.00	\$0
INDEPENDENT CLAIMS	2 –	3	0	x\$78.00	\$0
Total of above calculations =					\$0
Reduction by 50% for filing by small entity =					\$
TOTAL =					\$0



REISSUE PATENT APPLICATION TRANSMITTAL

Attorney Docket No. 201804

18. ☐ Please charge my Deposit Account No. 12-1216 in the amount of \$. A duplicate copy of this sheet is enclosed.
19. ☒ A check in the amount of \$838.00 is enclosed.
20. The Commissioner is hereby authorized to credit overpayments or charge any additional fees of the following types to Deposit Account No. 12-1216:
- a. ☒ Fees required under 37 CFR 1.16.
- b. ☒ Fees required under 37 CFR 1.17.

21. CORRESPONDENCE ADDRESS

Pamela J. Ruschau, Registration No. 34242
Leydig, Voit & Mayer, Ltd.
Two Prudential Plaza, Suite 4900
180 North Stetson
Chicago, Illinois 60601-6780
Telephone: (312) 616-5600
Facsimile: (312) 616-5700

Name	Pamela J. Ruschau
Signature	<i>Pamela J. Ruschau</i>
Date	August 23, 1999

Certificate of Mailing Under 37 C.F.R. 1.10

I hereby certify that this Reissue Patent Application Transmittal and all accompanying documents are being deposited with the United States Postal Service "Express Mail Post Office To Addressee" Service under 37 C.F.R. 1.10 on the date indicated below and is addressed to: Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.

<i>Brian D. Sandstrom</i>	<i>Brian D. Sandstrom</i>	August 23, 1999
Name of Person Signing	Signature	Date

REISSUE (Rev. 11/12/1998)

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

KUMP et al.

Serial No. Unassigned

Filed: Herewith

Reissue of U.S. Patent No. 5,660,946

Issued: August 26, 1997

Assigned to GNB Technologies, Inc.

For: SEALED LEAD-ACID CELLS AND
BATTERIES HAVING AN
EXPANDABLE COVER

ASSENT OF ASSIGNEE

Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

GNB TECHNOLOGIES, INC., the assignee of the entire right, title, and interest in the above-referenced United States Patent, hereby consents to the reissue thereof, application for which is being filed herewith.

GNB TECHNOLOGIES, INC.

Date: July 26, 1999



Thomas J. Smith
Vice President and Chief Financial Officer

055220" T 9062250

JC598 U.S. PTO
09/379051
08/23/99

KUMP et al.

Filed: Herewith

Issued: August 26, 1997

**For: SEALED LEAD-ACID CELLS AND
BATTERIES HAVING AN
EXPANDABLE COVER**

Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

1. Please prepare a certified Abstract of Title in respect of the above-identified original patent for placing in the official file of the above-identified Reissue application.
2. Title is vested in the name of GNB Technologies, Inc., a Delaware corporation, by virtue of an assignment recorded on September 25, 1996, at Reel 8152, Frame 162.
3. Please charge the fee required by 37 C.F.R. § 1.19(b)(2) and any deficiency in fees or additional fees in connection with this paper to Deposit Account No. 12-1216. A duplicate copy of this Request is attached.

Respectfully submitted,

Pamela J. Ruschan
Pamela J. Ruschan, Reg. No. 34242
One of the Attorneys for Applicant(s)
LEYDIG, VOIT & MAYER, LTD.
Two Prudential Plaza, Suite 4900
180 North Stetson
Chicago, Illinois 60601-6780
(312) 616-5600 (telephone)
(312) 616-5700 (facsimile)

Date: August 23, 1999

SEALED LEAD-ACID CELLS AND BATTERIES HAVING AN EXPANDABLE COVER

FIELD OF THE INVENTION

The present invention relates to lead-acid cells and batteries, and more particularly to such cells and batteries having an expandable cover capable of accommodating the grid growth which occurs in service.

BACKGROUND OF THE INVENTION

Sealed lead-acid cells and batteries, for many application, have significant advantages in comparison to the use of conventional, flooded lead-acid cells and batteries. Such cells and batteries, sometimes termed "VRLA" cells and batteries (i.e., valve-regulated, lead-acid), utilize bunsen valves and the like to maintain the desired internal pressure for an efficient oxygen recombination cycle.

Some applications where such sealed cells and batteries are used are termed stationary battery applications. In such applications, such cells and batteries are maintained at a full state-of-charge and in a ready-to-use condition, typically by floating at a constant preset voltage. Stationary cells and battery applications include use for stand-by or operational power, including telecommunications, utilities, emergency lighting for commercial buildings, stand-by power for cable television systems, and uninterruptible power supplies.

Such uninterruptible power supplies concern, for example, systems which back-up computers and communication networks. Having a reliable uninterruptible power source accommodates the orderly shutdown of computers when there is a sudden interruption in the primary power source, typically during an electrical power outage. Such an uninterruptible power source will also accommodate short, or intermittent, losses in power. In the event of a power interruption, the uninterruptible power source is subject to a rapid, and sometimes deep, discharge.

Another potential application for sealed lead-acid cells and batteries is a variety of motive power applications in which an array of cells or batteries provides the motive power for vehicles ranging from Class 1 to Class 3 trucks, various automated guided vehicles, mining vehicles and also railroad locomotives. The performance requirements for motive-powered vehicles are quite different from the performance requirements for stationary battery power sources. In stationary applications, the depth of discharge in service is relatively shallow, and the number of discharges is small, as most batteries are in float service. In direct contrast, motive power applications require relatively deep depths of discharge to be achieved on a continuous cycling basis over a period of time. Indeed, a common requirement for Class 1-3 trucks is that, in an 8-hour shift, the cell or battery assembly must be capable of delivering an 80% depth of discharge and that performance is required for about 300 cycles per year with a useful service life under those conditions of 4 or 5 years.

A common problem encountered by such VRLA cells and batteries is the integrity of the terminal seal over time as a result of grid growth which occurs in service. As has been especially common at the positive terminal, grid growth occurs as a battery grid corrodes over time, hence causing the battery terminal to move outwardly relative to the battery cover. This relative rise causes stress on both the required terminal-cover seal, as well as the requisite container-cover seal. As the container and cover are commonly made of plastic, each was known to fail in various ways, such as by

5 sealed lead-acid cells and batteries because relatively high internal temperatures in service can be reached. Such relatively high temperatures lead to an increase in the rate of grid corrosion which can result in significant grid growth.

10 This problem is not only well-known, but has also commanded substantial attention. A wide variety of attempted solutions have been proposed.

U.K. Patent 2026761A thus describes an assembly for securing a terminal post in a cover of an accumulator. The terminal post has a shank with circumferential ribs onto which a collar member is molded. The member has an upwardly-extending, annular neck by which the member is welded to a corresponding neck of the cover. The welded neck of the cell cover is joined to the cover by a flexible annular part made of a thin thermoplastic material in corrugated form.

Another attempt to solve the problems caused by terminal expansion is illustrated in U.S. Pat. No. 4,445,356 to Barrette, Jr. The '356 patent depicts a battery having a plastic bellows integrally molded or heat or sonically sealed to a battery cover at one end and either molded, heat or sonically sealed to a lead terminal extension or a plastic terminal sleeve at another end, wherein the plastic bellows is raised above the level of the battery cover and the terminal post passes through the plastic bellows.

Still another attempt to solve the terminal expansion problem is shown by U.S. Pat. No. 4,467,021 to Stocchiero. This patent utilizes a flexible, concave battery lid for distributing stress due to elongation of terminal poles, and the poles are shown welded to a bushing. As noted in his later patent, U.S. Pat. No. 4,898,795, Stocchiero indicates that the lid in his '021 configuration presents limited elasticity where its width is considerably reduced in relation to its length.

Yet another attempt to solve the problems caused by terminal expansion is disclosed in the aforementioned '795 patent. The '795 patent depicts an elastic diaphragm co-axially aligned with an accumulator pole below the surface of the lid. The elastic diaphragm is shown as having either a corrugated, bellows-shaped tube or toroidal shape. In one embodiment, a threaded bushing receives a threaded pole. In this same embodiment, the diaphragm is integrally attached to the lid at one edge, and as the bushing is tightened around the pole, the other edge of the diaphragm is locked between the threaded bushing and an O-ring, which O-ring is positioned between the threaded bushing and the pole. As opposed to the proposed solutions previously described wherein diaphragms were designed to operate by flexible expansion, the diaphragm in the '795 patent is intended to operate by collapsing.

5 Despite all of the prior efforts in this area, there still exists the need for a cover-seal configuration which can adequately accommodate the inevitable grid growth in use, but which also can be readily manufactured. A satisfactory configuration thus must be capable of being efficiently made while achieving the reliable and requisite seals.

Accordingly, it is a primary object of the present invention to provide sealed lead-acid cells and batteries whose integrity is not compromised in service as the inevitable grid growth takes place.

Another object of this invention is to provide a flexible, yet durable, cell or battery cover which is responsive to terminal post expansion so that, as grid growth occurs, the

Other objects and advantages of the present invention will be apparent as the following description proceeds, taken with the accompanying drawings.

In accordance with the present invention, a lead-acid cell or battery is provided which has an expandable cover configuration that accommodates the inevitable grid growth in service, but which maintains the required cover-to-container and terminal-to-cover seals. This cover configuration utilizes an expandable area surrounding at least the positive terminal which includes a first region accommodating a terminal-cover sealing assembly and a second region about the first region and having a position outward from the interior of the cell relative to the location of the first region. As grid growth occurs in service, the first region, together with the terminal-cover sealing assembly, move outwardly toward the outward position of the second region. In this fashion, the grid growth which occurs in service is accommodated without adversely affecting the reliability of either the terminal-cover or cover-container seals.

In one embodiment, the terminal-cover sealing assembly utilizes a seal nut as the outer-cell sealing member and a plastics member molded about the terminal post as the inner-cell sealing member. Another preferred embodiment includes the seal nut cooperating with an annular member formed about the terminal post as the inner-cell sealing member.

With either embodiment, manufacture and assembly can be reliably and efficiently carried out. As should be appreciated, this invention is susceptible to various modifications and alternative forms. However, it is not intended to limit the invention to the particular form disclosed, but, on the contrary, the invention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the invention as expressed in the appended claims. Thus, while the invention will be illustrated with sealed lead-acid cells and batteries, it should be appreciated that this invention is equally applicable to use with any cells or batteries wherein similar problems resulting from grid growth or the like occur and must be accommodated.

FIG. 2 is an enlarged, partial cross-sectional view of the cell/battery shown in FIG. 1, taken generally along line 2—2 in FIG. 1, illustrating one preferred cover and seal configuration; and

FIG. 3 is a partial cross-sectional view similar to FIG. 2 and showing another preferred embodiment at the cover and seal configuration.

FIG. 1 illustrates the sealed lead-acid cell/battery 10 of the present invention having an expandable cover 12. The

particular configuration of the cell or battery does not form a part of the present invention. Many configurations are known and may be used. Similarly, the specific components that are used in the cell or battery, other than the components associated with the expandable cover as will be described herein do not form a part of this invention. Any desirable components that fit the requirements for the intended application may be utilized, a wide variety of components having been used and are known. U.S. Pat. No. 4,401,730 to Szymborski et al. discloses an illustrative example of a suitable sealed lead-acid cell.

Pursuant to the present invention, FIGS. 1 and 2 illustrate a sealed lead-acid cell/battery having one preferred embodiment of an expandable cover according to the present invention. Thus, the cover 12 has a terminal opening 14 through which terminal post 16 protrudes. Preferably, and as is shown, the terminal post 16 has a series of rings 18 disposed and configured to provide a long tortuous path for electrolyte to migrate before any leakage could occur. The terminal end 20 of terminal post 16 extends a sufficient level above the cover 12 so as to allow adequate space for easy access for making the necessary electrical connection, but also to accommodate the above-cover member of the sealing assembly used.

In this embodiment, the terminal-cover sealing assembly includes a plastics member 22 which may be molded about terminal post 16, filling the space between rings 18. The above-cover annular part 24 of plastics member 22 has screw threads 26 for accepting a seal nut 28 that comprises the outer-cell sealing member of the terminal-cover sealing assembly. The bottom part of plastics member 22 terminates below the cover 12 and has an annular cantilever arm 30, having a groove 32 exposed to the cover opening 14. Cantilever arm 30 terminates at a location past the cover opening 14 so as to facilitate the terminal-cover sealing, as will be discussed hereinafter. The cantilever arm 30 in this embodiment comprises the inner-cell sealing member of the terminal-cover sealing assembly.

The material for the plastics member 22 can be any one useful for lead-acid cells. As an illustrative example, ethylene-polypropylene copolymers may be employed.

Seal nut 28 is threaded, as indicated at 34, complementally configured with threads 26 of the plastics member 22. Also, seal nut 28 includes a groove 38, dimensioned and positioned to form an annulus 40 with groove 32 of plastics member 22 about the terminal post 16.

The cover 12 includes a flange 42 which defines the cell opening 14, the flange being dimensioned so as to be positioned in annulus 40. The dimensions of flange 42 relative to annulus 40 should preferably be such that the flange 42 can be compressed and distended as seal nut 28 is screwed into its assembled position. It is thus preferred to have the flange 42 dimensions be slightly smaller than that of annulus 40. This arrangement retains the terminal, the cover and the sealing assembly in their desired relative location as grid growth occurs and the cover expands to accommodate the grid growth.

In accordance with a preferred aspect of the present invention, terminal-cover sealing is provided by a resilient seal or seals. The principal terminal-cover sealing is provided by a resilient seal located adjacent the inner surface of the cover. As shown in FIG. 2, first O-ring 44 is positioned in the plastics member 22 in seat 46 located in abutting contact with interior surface 48 of the cover 12. Second, O-ring 50, seated in seal nut O-ring seat 52, is positioned adjacent the outer surface 54 of cover 12. When seal nut 28

Most preferably, both the principal and supplemental seals are utilized. It is likewise most preferable to locate the outer and inner cover seals in alignment with each other, as may be appreciated. Any shape or configuration of seal may be used, and many suitable seals are known. As may be appreciated, a suitable O-ring must be acid-resistant and maintain the desired seal for the expected service life of the cell or battery.

The movement resulting from grid growth can be described as being upward movement when the sealed cell is used in an upright position in service. When positioned on its side in service, the movement is, of course, outward relative to the interior of the sealed cell.

FIG. 3 illustrates another preferred embodiment of the present invention. In this embodiment, the main components of the terminal-cover seal assembly shown in FIGS. 1 and 2 are identical, with one exception. In the FIG. 3 embodiment, the plastics member molded about the terminal post is eliminated, and the seal nut threads onto the terminal post and cooperates with a terminal annulus portion positioned adjacent the inner surface of the cover.

The sealing assembly includes an inner cell member 82 which has an annular cantilever arm 84 having a groove 86

exposed to the cover opening 74. Preferably, this interior sealing member can be cast integrally with the terminal post 76. Cantilever arm 84 terminates at a location past the cover opening 74, facilitating the terminal-cover sealing as described in conjunction with the initial embodiment. Seal nut 88 is threaded, as indicated at 90, so as to be threaded upon the terminal post 76. Seal nut 88 comprises the outer seal portion of the terminal-cover sealing assembly, cooperating with inner sealing member 82. As in the initial embodiment, seal nut 88 includes a groove 92 forming an annulus 94 with groove 104 of the inner sealing member 82.

Also, the cover 72 includes a flange 96 which defines the annular extent of the cover opening 74, the flange being dimensioned and positioned as previously described. Similarly, terminal-cover sealing is provided by internal and, when used, external resilient seals. The inner seal member 82 likewise includes a seat 104 accommodating an O-ring 106, which O-ring is retained in an abutting relationship with the inner surface 108 of the cover 72. As shown, O-ring 98 seated in seal nut O-ring seat 100 is positioned adjacent the outer surface 102 of the cover 72 and provides, when used, desirable supplemental sealing.

Similarly, the cover 72 is formed with an expandable area 110 having a first region 112 and a second region 114. Distention or flexing of this cover portion, as grid growth occurs, can be accommodated without disturbing the desired sealing as previously described in the embodiment of FIG. 2.

In both illustrative embodiments, the expandable cover area completely surrounds the terminal post, and this configuration is preferred. However, if desired, extending the area less than 360° is certainly within the scope of the invention. In such a configuration, it would be preferable to provide symmetrical segments (e.g., four 60° arcuate segments equidistantly positioned about the terminal post) to allow essentially symmetrical outward movement of the terminal-cover sealing assembly as grid growth occurs.

Also, while not forming a part of the present invention, the terminal, seal nut or other component could be coated with a sealing composition to minimize electrolyte leakage. Many such sealing compositions are known.

Further, while the sealing achieved in the illustrative embodiments is provided by O-rings located outboard from the cover flange, other positioning could be used. For example, an O-ring washer or the like could be positioned in the annulus formed by the outer and inner-cell sealing members. Such a configuration provides additional assurance that the flange is in a satisfactory sealing arrangement. Indeed, both configurations could be used together if desired.

The present invention thus provides a sealing assembly which not only effectively achieves the necessary terminal-cover sealing, but also does so in a fashion which accommodates the inevitable distention of the cover which occurs due to grid growth in service without disturbing either the terminal-cover or the cover-container seals. The sealing assembly components, including the cover for the sealed lead-acid cell/battery can be readily manufactured on an automated basis.

We claim:

1. A sealed lead-acid cell subject to grid growth during service comprising a container, a cover sealed to said container and having an inner and an outer surface and terminal openings, a positive and negative terminal extending above the height of the cover, an expandable cover area surrounding at least said terminal opening for said positive

terminal, a first region accommodating a terminal-cover sealing assembly, and a second region located about said first region and having a position outward from the interior of the cell relative to the location of said first region, a terminal-cover sealing assembly comprising inner and outer-cell sealing members, said cover having a flange surrounding said terminal opening for at least said positive terminal, said inner and outer-cell sealing members each having a groove together forming an annulus about at least said positive terminal in which said flange is seated, said outer-cell sealing member being threaded onto said terminal and retaining at least part of said first region between said outer-cell sealing and said inner-cell sealing members, and at least one of said inner and outer-cell sealing members having a resilient sealing means positioned between the respective said member and the respective surface of the cover, said lead-acid cell accommodating grid growth in service by allowing said first region to move toward the position of said second region aspect during service.

2. The cell of claim 1 wherein said inner and outer-cell sealing members each have a resilient sealing member.

3. The cell of claim 2 wherein each of said resilient seals comprises an O-ring seated in a groove and positioned about

65E2B0" 75062E60

the terminal with said flange being located between said O-rings and said terminals.

4. The cell of claim 3 wherein said outer-cell sealing member comprises a seal nut.

5 5. The cell of claim 4 wherein said inner-cell sealing member comprises an annular member cast with said terminal.

10 6. The cell of claim 1 wherein said expandable cover area is molded into said cover and, in cross-section, assumes a sinusoidal configuration in its assembled position prior to use in service.

7. The cell of claim 6 wherein the distance between said first and second regions is at least equal to the distance expected to be caused by the grid growth in service.

15 8. The cell of claim 2 wherein said outer-cell sealing member is threaded directly onto said terminal.

20 9. The cell of claim 2 wherein said terminal has a series of rings and includes a plastics member molded about said terminal, the molded plastics member filling the space between said rings and having a threaded outer surface, and said outer-cell sealing member being threaded about the outer threaded surface of said plastics member.

* * * * *

662200-15052660

10. A sealed lead-acid cell subject to grid growth during service comprising

a container,

a cover sealed to said container and having an inner and an outer surface and terminal openings,

a positive and negative terminal extending above the height of the cover, said terminals being sealed to the cover,

an expandable cover area surrounding at least said terminal opening for said positive terminal, whereby said expandable cover area may flex as grid growth occurs.

11. The battery of claim 10 wherein said expandable cover area is molded into said cover.

12. The battery of claim 10 wherein said expandable cover area may be outwardly distended as grid growth occurs without adversely affecting the seal between said at least one terminal and the cover .

13. The battery of 10 wherein the expandable cover area includes a first region positioned substantially about the periphery of said at least one terminal, and a second region positioned substantially concentrically and radially outward said first region.

14. The battery of claim 13 wherein said first region is substantially planar thereby facilitating sealing between the terminal and the cover.

15. The battery of claim 13 wherein said second region, in cross-section, assumes a sinusoidal configuration in its assembled position prior to use in service.

5522907505250

16. The battery of claim 10 wherein said expandable cover area, in cross-section, assumes a sinusoidal configuration in its assembled position prior to use in service.

17. The battery of claim 10 expandable cover area extends substantially 360° about said at least one terminal.

662207006460

[57]

ABSTRACT

Sealed lead-acid cells and batteries include an expandable cover capable of accommodating the grid growth which occurs in service, the expandable cover comprises a first region which expands outwardly toward a second region and a flange which defines the terminal opening, and the cells or batteries include a terminal cover sealing assembly comprising inner and outer-cell sealing members which together form an annulus in which the flange is seated and retain one or both include resilient seals such as an O-ring that provide a terminal-cover seal.

662280 15062260

~~5,700,246~~




FIG. 1




FIG. 2




FIG. 3

COMBINED DECLARATION AND POWER OF ATTORNEY

As below named inventor, I hereby declare that

This declaration is of the following type:

- ☐ original ☐ design ☐ supplemental
☐ national stage of PCT ☒ Reissue of U.S. Patent 5,660,946
☐ divisional ☐ continuation ☐ continuation-in-part

My residence, post office address, and citizenship are as stated below next to my name. I believe I am the original, first, and sole inventor (*if only one name is listed below*) or an original, first, and joint inventor (*if plural names are listed below*) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

SEALED LEAD-ACID CELLS AND BATTERIES HAVING AN
EXPANDABLE COVER

the specification of which:

- ☒ is attached hereto.
☐ was filed on _____ as Serial No. _____ and was amended on _____ (*if applicable*).
☐ was filed by Express Mail No. _____ as Serial No. not known yet, and was amended on _____ (*if applicable*).
☐ was described and claimed in PCT International Application No. _____ filed on _____ and as amended under PCT Article 19 on _____ (*if any*).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claim(s), as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed.

COUNTRY	APPLICATION	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 USC 119			
				YES		NO
				YES		NO
				YES		NO

I hereby claim the benefit pursuant to Title 35, United States Code, § 119(e) of the following United States provisional application(s):

PRIOR U.S. PROVISIONAL APPLICATIONS CLAIMING THE BENEFIT UNDER 35 USC 119(e)	
APPLICATION NO.	DATE OF FILING

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56 which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application.

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 USC 120					
U.S. APPLICATIONS			Status (<i>check one</i>)		
U.S. APPLICATIONS	U.S. FILING DATE		PATENTED	PENDING	ABANDONED
1. 0 /					
2. 0 /					
3. 0 /					
PCT APPLICATIONS DESIGNATING THE U.S.			Status (<i>check one</i>)		
PCT APPLICATION NO.	PCT FILING DATE	U.S. SERIAL NOS. ASSIGNED (if any)	PATENTED	PENDING	ABANDONED
4.					
5.					
6.					

DETAILS OF FOREIGN APPLICATIONS FROM WHICH PRIORITY CLAIMED UNDER 35 USC 119 FOR ABOVE LISTED U.S./PCT APPLICATIONS				
ABOVE APPLN. NO.	COUNTRY	APPLICATION NO.	DATE OF FILING (day, month, yr)	DATE OF ISSUE (day, month, yr)
1.				
2.				
3.				
4.				
5.				
6.				

As a named inventor, I hereby appoint the following attorneys to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Berton Scott Sheppard, Reg. 20922
James B. Muskall, Reg. 22797
Dennis R. Schlemmer, Reg. 24703
Gordon R. Coons, Reg. 20821
John E. Rosenquist, Reg. 26356
John W. Kozak, Reg. 25117
Charles S. Oslakovic, Reg. 27583
Mark E. Phelps, Reg. 28461
H. Michael Hartmann, Reg. 28423
Bruce M. Gagala, Reg. 28844
Charles H. Mottier, Reg. 30874
John Kilyk, Jr., Reg. 30763
Robert F. Green, Reg. 27555
John B. Conklin, Reg. 30369
James D. Zalewa, Reg. 27848
John M. Belz, Reg. 30359
Brett A. Hesterberg, Reg. 31837
Jeffrey A. Wyand, Reg. 29458

Paul J. Korniczky, Reg. 32849
Pamela J. Ruschau, Reg. 34242
Steven P. Petersen, 32927
John M. Augustyn, Reg. 33589
Christopher T. Griffith, Reg. 33392
Wesley O. Mueller, Reg. 33976
Jeremy M. Jay, Reg. 33587
Jeffrey B. Burgan, Reg. 35463
Eley O. Thompson, Reg. 36035
Mark Joy, Reg. 35562
Allen E. Hoover, Reg. 37354
David M. Airan, Reg. 38811
Michael H. Tobias, Reg. 32948
Xavier Pillai, Reg. 39799
Y. Kurt Chang, Reg. 41397
Gregory C. Bays, Reg. 40505
Carol Larcher, Reg. 35243

Steven H. Sklar, Reg. 42154
M. Daniel Hefner, Reg. 41826
Thomas A. Belush, Reg. 37090
Kenneth P. Spina, Reg. 43927
Gary R. Jarosik, Reg. 35906
Song Zhu, Reg. 44420
Joseph S. Ostroff, Reg. 39321
Jeffery J. Makeever, Reg. 37390
Salim A. Hasan, Reg. 38175
Richard A. Wulff, Reg. 42238
Jamison E. Lynch, Reg. 41168
Rattan Nath, Reg. 43827
Robert M. Gould, Reg. 43642
David J. Schodin, Reg. 41294
Paul L. Ahern, Reg. 17020
Theodore W. Anderson, Reg. 17035
Noel I. Smith, Reg. 18698

I further direct that correspondence concerning this application be directed to LEYDIG, VOIT & MAYER, LTD., Two Prudential Plaza, Suite 4900, 180 North Stetson, Chicago, Illinois 60601-6780, Telephone (312) 616-5600.

The undersigned inventors believe the original patent, U.S. Patent No. 5,660,946, to be partially inoperative by reason of claiming less than the undersigned had a right to claim. At least one error is now apparent to the applicants. With respect to the originally issued claims 1-9, these claims specify a seal lead-acid cell which includes an expandable cover area surrounding at least the terminal opening for the positive terminal, and a particularized terminal-cover sealing assembly arrangement. It is the belief of the undersigned that the present invention encompasses a sealed lead-acid cell comprising an expandable cover area, rather than only a sealed lead-acid cell comprising an expandable cover area and a particularized sealing arrangement. This error was made without any deceptive intent on the part of the applicants and was discovered only recently, during a review of the patent claims after the issuance of the patent. To rectify this error, the original independent claim 1 has been recast as independent claim 10 and added to the present application. The applicants have also included dependent claims 11-17 which more precisely define and describe the structure of the expandable cover area.

I hereby declare that all statements made herein of my own knowledge are true, that all statements made on information and belief are believed to be true, that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor: WILLIAM H. KUMP

Inventor's signature

Date

7-30-99

Country of Citizenship: United States of America

Residence: 21 Dorset Road, St. Paul, Minneapolis 55118

Post Office Address: 21 Dorset Road, St. Paul, Minneapolis 55118

Full name of second joint inventor, if any: DEBORAH HUKÉ

Inventor's signature

Date

8/14/99

Country of Citizenship: United States of America

Residence: ~~16827 Willow Lane, Prior Lake, Minnesota 55372~~ 15114 HWY 61 BLVD, WELCH MN 55089

Post Office Address: ~~16827 Willow Lane, Prior Lake, Minnesota 55372~~ PO BOX 152, WELCH MN 55089

Full name of **third joint inventor**, if any: EDWARD MATTAN

Inventor's signature Edward Mattan

Date 8/18/99

Country of Citizenship: United States of America

Residence: 1726 Howard Street, St. Charles, Illinois 60174

Post Office Address: 1726 Howard Street, St. Charles, Illinois 60174